Int. J. of Computers, Communications and Control, Vol. 3 (2008)
Suppl. issue: Proceedings of ICCCC 2008, pp. 11-16

arXiv:0804.2037v1 [cs.OH] 13 Apr 2008

Some properties of the regular asynchronous systems

Serban E. Vlad

Abstract

The asynchronous systems are the models of the asynchronous circuits from the digital electrical engineering. An asynchronous system f is a multi-valued function that assigns to each admissible input $u : \mathbf{R} \to \{0,1\}^m$ a set $f(u)$ of possible states $x \in f(u), x : \mathbf{R} \to \{0,1\}^n$. A special case of asynchronous system consists in the existence of a Boolean function $\Upsilon : \{0,1\}^n \times \{0,1\}^m \to \{0,1\}^n$ such that $\forall u, \forall x \in f(u)$, a certain equation involving Υ is fulfilled. Then Υ is called the generator function of f (Moisil used the terminology of network function) and we say that f is generated by Υ. The systems that have a generator function are called regular.

Our purpose is to continue the study of the generation of the asynchronous systems that was started in [2], [3].

Keywords: asynchronous system, regularity, generator function

1 Preliminaries

Notation 1. *Let be the arbitrary set* M. *The following notation will be useful:* $P^*(M) = \{M' | M' \subset M, M' \neq \emptyset\}$.

Definition 2. *The set* $\mathbf{B} = \{0,1\}$, *endowed with the order* $0 \leq 1$ *and with the usual laws* $\overline{}, \cdot, \cup, \oplus$, *is called the **binary Boole algebra**.*

Definition 3. *The **initial value*** $x(-\infty + 0) \in \mathbf{B}^n$ *of the function* $x : \mathbf{R} \to \mathbf{B}^n$ *is defined by* $\exists t' \in \mathbf{R}, \forall t < t', x(t) = x(-\infty + 0)$.

Definition 4. *The **characteristic function*** $\chi_A : \mathbf{R} \to \mathbf{B}$ *of the set* $A \subset \mathbf{R}$ *is given by* $\forall t \in \mathbf{R}, \chi_A(t) = \begin{cases} 1, t \in A \\ 0, \ else \end{cases}$.

Notation 5. *We use the notation* $Seq = \{(t_k) | t_k \in \mathbf{R}, k \in \mathbf{N},\ t_0 < ... < t_k < ...$ *is unbounded from above*$\}$.

Definition 6. *A function* $x : \mathbf{R} \to \mathbf{B}^n$ *is called* $n-$***signal**, *shortly* ***signal*** *if* $\mu \in B^n$ *and* $(t_k) \in Seq$ *exist such that*

$$x(t) = \mu \cdot \chi_{(-\infty,t_0)}(t) \oplus x(t_0) \cdot \chi_{[t_0,t_1)}(t) \oplus ... \oplus x(t_k) \cdot \chi_{[t_k,t_{k+1})}(t) \oplus ... \quad (1)$$

The set of the $n-$*signals is denoted by* $S^{(n)}$.

Remark 7. *Let be* $x : \mathbf{R} \to \mathbf{B}^n, u : \mathbf{R} \to \mathbf{B}^m$. *Instead of* $x \times u : \mathbf{R} \times \mathbf{R} \to \mathbf{B}^n \times \mathbf{B}^m$ *we define the function* $x \times u$, *many times denoted by* (x,u), *as* $x \times u : \mathbf{R} \to \mathbf{B}^n \times \mathbf{B}^m$ *due to the existence of a unique time variable* $t \in \mathbf{R}$. *Between the consequences derived from here we have the identifications* $S^{(n)} \times S^{(m)} = S^{(n+m)}$ *and* $P^*(S^{(n)}) \times P^*(S^{(m)}) = P^*(S^{(n+m)})$.

Definition 8. *The **left limit** $x(t-0)$ of $x(t)$ from (1) is the* $\mathbf{R} \to \mathbf{B}^n$ *function defined as* $x(t-0) = \mu \cdot \chi_{(-\infty,t_0]}(t) \oplus x(t_0) \cdot \chi_{(t_0,t_1]}(t) \oplus ... \oplus x(t_k) \cdot \chi_{(t_k,t_{k+1}]}(t) \oplus ...$

Definition 9. *Let be* $U \in P^*(S^{(m)})$. *A multi-valued function* $f : U \to P^*(S^{(n)})$ *is called **asynchronous system**, shortly **system**. Any* $u \in U$ *is called (**admissible**) **input** and the functions* $x \in f(u)$ *are called (**possible**) **states**.*

Remark 10. *The asynchronous systems are the models of the asynchronous circuits. The multi-valued character of the cause-effect association is due to the statistical fluctuations in the fabrication process, the variations in the ambiental temperature, the power supply etc. Sometimes the systems are given by equations and/or inequalities.*

Definition 11. *The **initial state function** of* f *is by definition the function* $i_f : U \to P^*(\mathbf{B}^n), \forall u \in U, i_f(u) = \{x(-\infty+0) | x \in f(u)\}$.

Definition 12. *The function* $\rho : \mathbf{R} \to \mathbf{B}^n$ *is called **progressive** if* $(t_k) \in Seq$ *exists such that* $\rho(t) = \rho(t_0) \cdot \chi_{\{t_0\}}(t) \oplus ... \oplus \rho(t_k) \cdot \chi_{\{t_k\}}(t) \oplus ...$ *and* $\forall i \in \{1,...,n\}$, *the set* $\{k | k \in \mathbf{N}, \rho_i(t_k) = 1\}$ *is infinite. The set of the progressive functions is denoted by* P_n.

Notation 13. *Let be* $\Upsilon : \mathbf{B}^n \times \mathbf{B}^m \to \mathbf{B}^n, u \in S^{(m)}$, $\mu \in \mathbf{B}^n$ *and* $\rho \in P_n$. *The solution of the equation*

$$\begin{cases} x(-\infty+0) = \mu \\ \forall i \in \{1,...,n\}, x_i(t) = \begin{cases} \Upsilon_i(x(t-0), u(t-0)), if\ \rho_i(t) = 1 \\ x_i(t-0), otherwise \end{cases} \end{cases} \tag{2}$$

is denoted by $\Upsilon^{-\rho}(t,\mu,u)$.

Definition 14. *The system* $\Sigma_\Upsilon^- : S^{(m)} \to P^*(S^{(n)}), \forall u \in S^{(m)}, \Sigma_\Upsilon^-(u) = \{\Upsilon^{-\rho}(t,\mu,u) | \mu \in \mathbf{B}^n, \rho \in P_n\}$ *is called the **universal regular asynchronous system** that is generated by the function* Υ.

Definition 15. *The system* f *is called **regular** if* Υ *exists such that* $\forall u \in U, f(u) \subset \Sigma_\Upsilon^-(u)$. *If so,* Υ *is called the **generator function** of* f *and we also say that* Υ ***generates*** f.

Remark 16. *Equation (2) shows how the circuits compute asynchronously the Boolean function* Υ *: the computation is made at the discrete time instances* $\{t_k | k \in \mathbf{N}, \exists i \in \{1,...,n\}, \rho_i(t_k) = 1\}$ *on these coordinates* Υ_i *for which* $\rho_i(t_k) = 1$. *The models of these circuits, the systems* f *with the generator function* Υ, *have the remarkable property that a function* $\pi_f : W_f \to P^*(P_n)$ *exists,* $W_f = \{(x(-\infty+0), u) | u \in U, x \in f(u)\}$ *such that* $\forall u \in U, f(u) = \{\Upsilon^{-\rho}(t,\mu,u) | \mu \in i_f(u), \rho \in \pi_f(\mu,u)\}$. π_f *is called the **computation function** of* f. *For* f *regular,* Υ *and* π_f *are not unique.*

2 Subsystems

Definition 17. *The system* f *is called a **subsystem** of* $g : V \to P^*(S^{(n)})$, $V \in P^*(S^{(m)})$ *and we write* $f \subset g$, *if* $U \subset V$ *and* $\forall u \in U, f(u) \subset g(u)$.

Remark 18. *We interpret* $f \subset g$ *in the following way: the systems* f *and* g *model the same circuit, but the model represented by* f *is more precise than the model represented by* g.

Theorem 19. *The function* Υ *and the regular systems* $f \subset \Sigma_\Upsilon^-$, $g \subset \Sigma_\Upsilon^-$ *are given. We denote by* $i_g : V \to P^*(\mathbf{B}^n)$ *the initial state function and by* $\pi_g : W_g \to P^*(P_n)$ *the computation function of* g. *The following statements are equivalent:*

a) $f \subset g$

b) $U \subset V$ *and* $\forall u \in U, i_f(u) \subset i_g(u)$ *and* $\forall u \in U, \forall \mu \in i_f(u), \forall \rho \in \pi_f(\mu,u), \exists \rho' \in \pi_g(\mu,u), \Upsilon^{-\rho}(t,\mu,u) = \Upsilon^{-\rho'}(t,\mu,u)$.

3 Dual systems

Definition 20. *The* ***dual*** *function* $\Upsilon^* : \mathbf{B}^n \times \mathbf{B}^m \to \mathbf{B}^n$ *of* Υ *is defined by* $\forall(\mu,\nu) \in \mathbf{B}^n \times \mathbf{B}^m, \Upsilon^*(\mu,\nu) = \overline{\Upsilon(\overline{\mu},\overline{\nu})}$. *Here the bar* $\overline{\mu}$ *refers to the complement done coordinatewise.*

Definition 21. *The* ***dual*** *of the system* f *is by definition the system* $f^* : U^* \to P^*(S^{(n)})$, *where* $U^* = \{\overline{u} | u \in U\}$ *and* $\forall u \in U^*, f^*(u) = \{\overline{x} | x \in f(\overline{u})\}$.

Remark 22. *The system* f^* *models the circuit modeled by* f *with the AND gates replaced by OR gates etc.*

Notation 23. *We denote* $i_{f^*} : U^* \to P^*(\mathbf{B}^n)$, $\forall u \in U^*, i_{f^*}(u) = \{\overline{\mu} | \mu \in i_f(\overline{u})\}$.

Notation 24. *We denote by* $\pi_{f^*} : W_{f^*} \to P^*(P_n)$ *where* $W_{f^*} = \{(\overline{x(-\infty+0)}, u) | u \in U^*, x \in f(\overline{u})\}$ *the function* $\forall(\mu,u) \in W_{f^*}, \pi_{f^*}(\mu,u) = \pi_f(\overline{\mu},\overline{u})$.

Theorem 25. *The dual system* f^* *of* $f \subset \Sigma^{-}_{\Upsilon}$ *is regular,* $f^* \subset \Sigma^{-}_{\Upsilon^*}$; *its initial state function is* i_{f^*} *and its computation function is* π_{f^*}.

4 Cartesian product

Definition 26. *The* ***Cartesian product*** *of the systems* f *and* $f' : U' \to P^*(S^{(n')}), U' \in P^*(S^{(m')})$ *is defined as* $f \times f' : U \times U' \to P^*(S^{(n+n')})$, $\forall(u,u') \in U \times U', (f \times f')(u,u') = f(u) \times f'(u')$.

Remark 27. *The Cartesian product* $f \times f'$ *models two circuits that run independently on each other.*

Notation 28. *For* Υ *and* $\Upsilon' : \mathbf{B}^{n'} \times \mathbf{B}^{m'} \to \mathbf{B}^{n'}$, *we denote by* $\Upsilon \times \Upsilon' : \mathbf{B}^{n+n'} \times \mathbf{B}^{m+m'} \to \mathbf{B}^{n+n'}$ *the function* $\forall((\mu,\mu'),(\nu,\nu')) \in \mathbf{B}^{n+n'} \times \mathbf{B}^{m+m'}, (\Upsilon \times \Upsilon')((\mu,\mu'),(\nu,\nu')) = (\Upsilon(\mu,\nu), \Upsilon'(\mu',\nu'))$. *In this notation we identify* $(\mu,\mu') \in \mathbf{B}^n \times \mathbf{B}^{n'}$ *with* $(\mu_1,...,\mu_n,\mu'_1,...,\mu'_{n'}) \in \mathbf{B}^{n+n'}$ *etc.*

Notation 29. *If* $i_{f'} : U' \to P^*(\mathbf{B}^{n'})$ *is the initial state function of* f', *we use the notation* $i_{f \times f'} : U \times U' \to P^*(\mathbf{B}^{n+n'}), \forall(u,u') \in U \times U', i_{f \times f'}(u,u') = i_f(u) \times i_{f'}(u')$.

Notation 30. *The regular systems* f, f' *are given,* $f \subset \Sigma_{\Upsilon}$, $f' \subset \Sigma_{\Upsilon'}$ *as well as their computation functions:* $\pi_f : W_f \to P^*(P_n)$, $\pi_{f'} : W_{f'} \to P^*(P_{n'})$. *We denote by* $\pi_{f \times f'} : W_{f \times f'} \to P^*(P_{n+n'})$ *the function* $W_{f \times f'} = \{((x(-\infty+0), x'(-\infty+0)), (u,u')) | (u,u') \in U \times U', (x,x') \in f(u) \times f'(u')\}, \forall((\mu,\mu'),(u,u')) \in W_{f \times f'}$, $\pi_{f \times f'}((\mu,\mu'),(u,u')) = \pi_f(\mu,u) \times \pi_{f'}(\mu',u')$.

Remark 31. *The function* $\pi_{f \times f'}$ *is correctly defined since* $\forall\rho, \forall\rho', \rho \in P_n$ *and* $\rho' \in P_{n'} \Longrightarrow (\rho,\rho') \in P_{n+n'}$.

Theorem 32. *If* $f \subset \Sigma^{-}_{\Upsilon}, f' \subset \Sigma^{-}_{\Upsilon'}$, *then the system* $f \times f'$ *is regular,* $f \times f' \subset \Sigma^{-}_{\Upsilon \times \Upsilon'}$; *its initial state function is* $i_{f \times f'}$ *and its computation function is* $\pi_{f \times f'}$.

5 Parallel connection

Definition 33. *The* ***parallel connection*** *of* f *and* $f'_1 : U'_1 \to P^*(S^{(n')})$, $U'_1 \in P^*(S^{(m)})$ *is defined whenever* $U \cap U'_1 \neq \emptyset$ *by* $f || f'_1 : U \cap U'_1 \to P^*(S^{(n+n')})$, $\forall u \in U \cap U'_1, (f || f'_1)(u) = f(u) \times f'_1(u)$.

Remark 34. *The parallel connection* $f || f'_1$ *models two circuits that run under the same input, independently on each other.*

Notation 35. *Let be* Υ *and* $\Upsilon'_1 : \mathbf{B}^{n'} \times \mathbf{B}^m \to \mathbf{B}^{n'}$*, for which we denote by* $\Upsilon || \Upsilon'_1 : \mathbf{B}^{n+n'} \times \mathbf{B}^m \to \mathbf{B}^{n+n'}$ *the function* $\forall((\mu,\mu'),\nu) \in \mathbf{B}^{n+n'} \times \mathbf{B}^m, (\Upsilon || \Upsilon'_1)((\mu,\mu'),\nu) = (\Upsilon(\mu,\nu), \Upsilon'_1(\mu',\nu))$*.*

Notation 36. *Let* $i_{f'_1} : U'_1 \to P^*(\mathbf{B}^{n'})$ *be the initial state function of* f'_1*. If* $U \cap U'_1 \neq \emptyset$*, we use the notation* $i_{f||f'_1} : U \cap U'_1 \to P^*(\mathbf{B}^{n+n'}), \forall u \in U \cap U'_1, i_{f||f'_1}(u) = i_f(u) \times i_{f'_1}(u)$*.*

Notation 37. *We suppose that the systems* f*,* f'_1 *are regular i.e.* $f \subset \Sigma^-_{\Upsilon}, f'_1 \subset \Sigma^-_{\Upsilon'_1}$ *and let* $\pi_f : W_f \to P^*(P_n), \pi_{f'_1} : W_{f'_1} \to P^*(P_{n'})$ *be their computation functions. If* $U \cap U'_1 \neq \emptyset$*, then we use the notation* $\pi_{f||f'_1} : W_{f||f'_1} \to P^*(P_{n+n'})$*,* $W_{f||f'_1} = \{((x(-\infty+0), x'(-\infty+0)), u) | u \in U \cap U'_1, x \in f(u), x' \in f'_1(u)\}$*,* $\forall((\mu,\mu'),u) \in W_{f||f'_1}, \pi_{f||f'_1}((\mu,\mu'),u) = \pi_f(\mu,u) \times \pi_{f'_1}(\mu',u)$*.*

Theorem 38. *If* $f \subset \Sigma^-_{\Upsilon}$*,* $f'_1 \subset \Sigma^-_{\Upsilon'_1}$ *and* $U \cap U'_1 \neq \emptyset$*, then* $f||f'_1 \subset \Sigma^-_{\Upsilon||\Upsilon'_1}$*; its initial state function is* $i_{f||f'_1}$ *and its computation function is* $\pi_{f||f'_1}$*.*

6 Serial connection

Remark 39. *Let be the systems* f *and* $h : X \to P^*(S^{(p)}), X \in P^*(S^{(n)})$*. When* $\bigcup\limits_{u \in U} f(u) \subset X$*, the serial connection of* f *and* h *is defined by* $h \circ f : U \to P^*(S^{(p)}), \forall u \in U, (h \circ f)(u) = \bigcup\limits_{x \in f(u)} h(x)$*. If* f *and* h *are regular, this definition means that in the systems of equations*

$$\left\{ \begin{array}{c} x(-\infty+0) = \mu \\ \forall i \in \{1,...,n\}, x_i(t) = \left\{ \begin{array}{c} \Upsilon_i(x(t-0), u(t-0)), if\ \rho_i(t) = 1 \\ x_i(t-0), otherwise \end{array} \right. \end{array} \right. , \tag{3}$$

$$\left\{ \begin{array}{c} y(-\infty+0) = \lambda \\ \forall j \in \{1,...,p\}, y_j(t) = \left\{ \begin{array}{c} \vartheta_j(y(t-0), x(t-0)), if\ \varpi_j(t) = 1 \\ y_j(t-0), otherwise \end{array} \right. \end{array} \right. \tag{4}$$

where $u \in S^{(m)}, x \in S^{(n)}, y \in S^{(p)}, \mu \in \mathbf{B}^n$*,* $\lambda \in \mathbf{B}^p$*,* $\rho \in P_n$*,* $\varpi \in P_p$*,* $\Upsilon : \mathbf{B}^n \times \mathbf{B}^m \to \mathbf{B}^n$*,* $\vartheta : \mathbf{B}^p \times \mathbf{B}^n \to \mathbf{B}^p$ *we eliminate* x*. Because this does not give any information of the regularity of* $h \circ f$*, we choose to work with a slightly different system from* $h \circ f$*, for which* x *is not eliminated.*

Notation 40. *If* f *and* h *fulfill* $\bigcup\limits_{u \in U} f(u) \subset X$*, then we denote by* $h * f : U \to P^*(S^{(n+p)})$ *the system* $\forall u \in U, (h * f)(u) = \{(x,y) | x \in f(u), y \in h(x)\}$*.*

Notation 41. *The function* $\vartheta * \Upsilon : \mathbf{B}^{n+p} \times \mathbf{B}^m \to \mathbf{B}^{n+p}$ *is defined by* $\forall((\mu,\lambda),\nu) \in \mathbf{B}^{n+p} \times \mathbf{B}^m, (\vartheta * \Upsilon)((\mu,\lambda),\nu) = (\Upsilon(\mu,\nu), \vartheta(\lambda, \Upsilon(\mu,\nu)))$*.*

Remark 42. *The point is that, instead of eliminating* x *in (3), (4) as* $h \circ f$ *does, we can work with* $h * f$ *and with the equation*

$$\left\{ \begin{array}{c} z(-\infty+0) = (\mu,\lambda) \\ \forall k \in \{1,...,n+p\}, z_k(t) = \left\{ \begin{array}{c} (\vartheta * \Upsilon)_k(z(t-0), u(t-0)), if\ (\rho,\varpi)_k(t) = 1 \\ z_k(t-0), otherwise \end{array} \right. \end{array} \right.$$

where $z \in S^{(n+p)}$*.*

Notation 43. *For* $i_h : X \to P^*(\mathbf{B}^p)$ *the initial state function of* h*, we denote by* $i_{h*f} : U \to P^*(\mathbf{B}^{n+p})$ *the function* $\forall u \in U, i_{h*f}(u) = \{(\mu,\lambda) | \mu \in i_f(u), \lambda \in \bigcup\limits_{x \in f(u), x(-\infty+0)=\mu} i_h(x)\}$*.*

Notation 44. *We suppose that* $\pi_h : W_h \to P^*(P_p)$ *is the computation function of* h, $W_h = \{(y(-\infty+0),x)|x \in X, y \in h(x)\}$. *We denote by* $\pi_{h*f} : W_{h*f} \to P^*(P_{n+p})$ *the function* $W_{h*f} = \{((x(-\infty+0),y(-\infty+0)),u)|u \in U, x \in f(u), y \in h(x)\}$, $\forall((\mu,\lambda),u) \in W_{h*f}$, $\pi_{h*f}((\mu,\lambda),u) = \{(\rho,\varpi)|\rho \in \pi_f(\mu,u), \varpi \in \bigcup\limits_{x \in f(u), x(-\infty+0)=\mu} \pi_h(\lambda,x)\}$.

Theorem 45. *The systems* f *and* h *are given such that the inclusion* $\bigcup\limits_{u \in U} f(u) \subset X$ *is true. If the regularity properties* $f \subset \Sigma^-_{\Upsilon}, h \subset \Sigma^-_{\vartheta}$ *hold, then* $h*f \subset \Sigma^-_{\vartheta*\Upsilon}$; *the initial state function of* $h*f$ *is* i_{h*f} *and its computation function is* π_{h*f}.

7 Intersection

Definition 46. *The **intersection** of* $f : U \to P^*(S^{(n)})$ *and* $g : V \to P^*(S^{(n)}), U, V \in P^*(S^{(m)})$ *is defined whenever* $\exists u \in U \cap V, f(u) \cap g(u) \neq \emptyset$ *by* $f \cap g : W \to P^*(S^{(n)})$, $W = \{u|u \in U \cap V, f(u) \cap g(u) \neq \emptyset\}$, $\forall u \in W, (f \cap g)(u) = f(u) \cap g(u)$.

Remark 47. *The intersection of two systems is a model that results by the simultaneous validity of two compatible models.*

Notation 48. *When* $W \neq \emptyset$, *we use the notation* $i_{f \cap g} : W \to P^*(\mathbf{B}^n), \forall u \in W, i_{f\cap g}(u) = i_f(u) \cap i_g(u)$.

Notation 49. *We consider the regular systems* f, g *for which the generator function* $\Upsilon : \mathbf{B}^n \times \mathbf{B}^m \to \mathbf{B}^n$ *is given such that* $f \subset \Sigma^-_{\Upsilon}, g \subset \Sigma^-_{\Upsilon}$. *Their computation functions are* $\pi_f : W_f \to P^*(P_n)$, $\pi_g : W_g \to P^*(P_n)$. *If the set* W *is non-empty, then we use the notation* $\pi_{f\cap g} : W_{f\cap g} \to P^*(P_n)$ *for the function that is defined by* $W_{f\cap g} = \{(x(-\infty+0),u)|u \in W, x \in f(u) \cap g(u)\}, \forall(\mu,u) \in W_{f\cap g}$, $\pi_{f\cap g}(\mu,u) = \{\rho|\rho \in \pi_f(\mu,u), \exists\rho' \in \pi_g(\mu,u), \Upsilon^{-\rho}(t,\mu,u) = \Upsilon^{-\rho'}(t,\mu,u)\}$.

Remark 50. *We remark the satisfaction of the following property of symmetry:* $W_{f\cap g} = W_{g\cap f}$ *and* $\forall(\mu,u) \in W_{f\cap g}, \forall\rho \in \pi_{f\cap g}(\mu,u), \exists\rho' \in \pi_{g\cap f}(\mu,u), \Upsilon^{-\rho}(t,\mu,u) = \Upsilon^{-\rho'}(t,\mu,u)$ *and* $\forall\rho' \in \pi_{g\cap f}(\mu,u), \exists\rho \in \pi_{f\cap g}(\mu,u), \Upsilon^{-\rho'}(t,\mu,u) = \Upsilon^{-\rho}(t,\mu,u)$.

Theorem 51. *If the regular systems* $f \subset \Sigma^-_{\Upsilon}, g \subset \Sigma^-_{\Upsilon}$ *fulfill* $W \neq \emptyset$, *then their intersection* $f \cap g : W \to P^*(S^{(n)})$ *is regular* $f \cap g \subset \Sigma^-_{\Upsilon}$; *its initial state function is* $i_{f\cap g}$ *and its computation function is* $\pi_{f\cap g}$.

8 Union

Definition 52. *The **union** of* f, g *is defined by* $f \cup g : U \cup V \to P^*(S^{(n)})$, $\forall u \in U \cup V, (f \cup g)(u) =$

$$\begin{cases} f(u), u \in U \setminus V, \\ g(u), u \in V \setminus U, \\ f(u) \cup g(u), u \in U \cap V \end{cases}.$$

Remark 53. *The union of the systems represents the validity of one of two models. This is useful for example in testing, when* f *is the model of the 'good' circuit and* g *is the model of the 'bad' circuit.*

Notation 54. *We denote by* $i_{f\cup g} : U \cup V \to P^*(\mathbf{B}^n)$ *the function* $\forall u \in U \cup V, i_{f\cup g}(u) =$

$$\begin{cases} i_f(u), u \in U \setminus V, \\ i_g(u), u \in V \setminus U, \\ i_f(u) \cup i_g(u), u \in U \cap V \end{cases}.$$

Lemma 55. *The sets* $W_f = \{(x(-\infty+0),u) | u \in U, x \in f(u)\}$, $W_g = \{(x(-\infty+0),u) | u \in V, x \in g(u)\}$, $W_{f\cup g} = \{(x(-\infty+0),u) | u \in U \cup V, x \in (f \cup g)(u)\}$ *fulfill* $W_{f\cup g} = W_f \cup W_g$.

Notation 56. *Let be the regular systems* f, g *and the function* Υ *such that* $f \subset \Sigma_\Upsilon^-, g \subset \Sigma_\Upsilon^-$ *are true. The computation functions of* f, g *are* π_f, π_g. *We denote by* $\pi_{f\cup g} : W_{f\cup g} \to P^*(P_n)$ *the function* $\forall(\mu,u) \in W_{f\cup g}$, $\pi_{f\cup g}(\mu,u) = \begin{cases} \pi_f(\mu,u), (\mu,u) \in W_f \setminus W_g, \\ \pi_g(\mu,u), (\mu,u) \in W_g \setminus W_f, \\ \pi_f(\mu,u) \cup \pi_g(\mu,u), (\mu,u) \in W_f \cap W_g \end{cases}$.

Theorem 57. *If the systems* f, g *are regular* $f \subset \Sigma_\Upsilon^-, g \subset \Sigma_\Upsilon^-$, *then the union* $f \cup g : U \cup V \to P^*(S^{(n)})$ *is regular,* $f \cup g \subset \Sigma_\Upsilon^-$; *its initial state function is* $i_{f\cup g}$ *and its computation function is* $\pi_{f\cup g}$.

References

[1] S. E. Vlad, *Teoria sistemelor asincrone,* Editura Pamantul Pitesti and WSEAS Press Athens, 2007.

[2] S. E. Vlad, "Boolean dynamical systems", *the 15-th Conference on Applied and Industrial Mathematics CAIM 2007, Mioveni, Romania, October 12-14*, 2007.

[3] S. E. Vlad, "On the generation of the asynchronous systems", *the first National Conference of Applied and Fundamental Mathematics, Iasi, Romania, November 9-10*, 2007.

Serban E. Vlad
Oradea City Hall
Computers Department
Piata Unirii, Nr. 1, 410100, Oradea, Romania
E-mail: serban_e_vlad@yahoo.com
Received: December 24, 2007